

345 HD Pedestrian Aerator



Internet

www.groundsmanindustries.com info@groundsmanindustries.com

Telephone

UK: 028 2766 7049

Int: +44(0) 28 2766 7049

Fax

UK: 028 2766 6855

Int: +44(0) 28 2766 6855

Address

30 Ballybrakes Road Ballymoney Co. Antrim Northern Ireland United Kingdom

Uk & Ireland Distributor's

Ireland & Scotland Groundsman Industries Phone +44(0) 28 2766 7049 www.groundsmanindustries.com

England & Wales Synergy Products Ltd Phone +44(0) 1380 828 337 www.synergyproducts.co.uk

Other Country's

Please See The Links Page On Our Web Site











Model 345 HD

Features

- GROUNDSMAN'S rugged sealed bearing mechanism is maintenance free and carries a 24 month factory warranty.
- Crank driven plunge action mechanism, punches double the density of holes in your green than the old roll-over machines and to a guaranteed depth.
- The number one proven, robust, high performance aerator for bowling greens.
- Fast coverage, up to 1200 sq yds / hour. (aerate your green in under 2 hours)
- Quick change Hollow, Solid, Chisel, Needle and Micro Tines to perform complete year round aeration, thatch removal and over-seeding.
- Clean efficient plunge action, depth adjustable up to 5" (150mm).

The professionals choice

Designed and produced by Groundsman Industries Patented Product





Internet

4

www.groundsmanindustries.com info@groundsmanindustries.com

Telephone



UK: 028 2766 7049

Int: +44(0) 28 2766 7049

Fax



UK: 028 2766 6855

Int: +44(0) 28 2766 6855

Address



30 Ballybrakes Road Ballymoney Co. Antrim Northern Ireland United Kingdom

Uk & Ireland Distributor's

Ireland & Scotland Groundsman Industries Phone +44(0) 28 2766 7049 www.groundsmanindustries.com

England & Wales Synergy Products Ltd Phone +44(0) 1380 828 337 www.synergyproducts.co.uk

Other Country's

Please See The Links Page On Our Web Site

Technical Specifications

TURF AERATORS Model 345HD

Swath 450mm (18") HD Weight 160kg (352 lbs)

Overall Dimensions:

Width 78cm (31")	Length	148cm (58")
------------------	--------	-------------

Height 91cm (36")

Engine 5.5 HP Honda GX160

Drive Single vee-belt and chain (O-Ring Sealed)

Mechanism Sealed bearing crank driven elliptical plunge action

PERFORMANCE CHART

Aeration Pattern	Forward Speed	Coverage	Penetration
75mm (3") Centres	38m/min	1026m ² /hr	130mm max
(Twin Holder)	(42 yds)	(1260 sq yds)	(5") max

*NOTE

Aeration patterns given are with twin holders. Triple, Quadra and Cluster holders give denser patterns accordingly.

The professionals choice

